NSN 4820-01-231-2698

Gate Valve - Page 1 of 2

Flange Diameter:



View Online at https://aerobasegroup.com/nsn/4820-01-231-2698

10.000 inches
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8
Valve Operation Method:
Manual
Connection Type:
Flange, round w/holes
Features Provided:
Bonnet packing
Valve Size:
5.000 inches
Maximum Operating Pressure And Media For Which Designed:
125.0 pounds per square inch steam and 200.0 pounds per square inch water-oil-gas
Stem Type:
Rising
Maximum Operating Tempurature And Media For Which Designed:
450.0 degrees fahrenheit steam and 150.0 degrees fahrenheit water-oil-gas
Face To Face Distance:
10.000 inches
Flange Face Design:
Plain
Inlet Relationship With Outlet:
Identical
Pressure Class:
125.0 pounds
Special Features:
Yoke interal with bonnet
Material:
Iron cast uns f12102 disk
Material Specification:
Astmb-62 assn standard single material response seat
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-01-231-2698

Gate Valve - Page 2 of 2



Fiig:

A500a0