

View Online at <https://aerobasegroup.com/nsn/4820-01-231-2704>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

8 all ends

**Maximum Operating Temp:**

450.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

5.000 inches

**Maximum Operating Pressure:**

200.0 pounds per square inch 2nd response

**Outside Diameter:**

10.000 inches all ends

**Face To Face Distance:**

13.000 inches

**Thickness:**

0.938 inches all ends

**Bolt Hole Diameter:**

0.875 inches all ends

**Bolt Circle Diameter:**

8.500 inches all ends

**Flange Face Design:**

Plain all ends

**Material:**

Iron cast body

**Material Specification:**

Astm b-6 (b) assn standard single material response flow control device

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

A1a straight through flanged ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0