

View Online at <https://aerobasegroup.com/nsn/4820-01-231-6999>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

6 2nd end

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

4.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Opening Pressure Setting:

150.0 pounds per square inch

Outside Diameter:

7.688 inches 1st end

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

6.625 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

5.500 inches

Bolt Circle Diameter:

6.562 inches 1st end

Flange Face Design:

Plain all ends

Special Features:

Non ferrous; navy flange

Material:

Nickel alloy flow control device

Material Specification:

Astm b61 assn standard single material response body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

C1a angle flanged ends

Furnished Items And Quantity:

1 lever

Specification Data:

81349-mil-v-24332 government specification

Specification Or Standard:

B grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.