

View Online at <https://aerobasegroup.com/nsn/4820-01-233-0757>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal

Valve Size:

2.500 inches

Maximum Operating Pressure:

250.0 pounds per square inch single response

Outside Diameter:

6.125 inches all ends

Thickness:

0.938 inches all ends

First Connection Face To Centerline Distance:

4.500 inches

Bolt Hole Diameter:

0.688 inches all ends

Second Connection Face To Centerline Distance:

4.500 inches

Bolt Circle Diameter:

5.000 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Material Specification:

Qq-n-288 federal specification single material response packing

Media For Which Designed:

Water, salt single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-b-16541 spec.