# NSN 4820-01-233-4773

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-233-4773

## Flow Control Device:

Piston

Bonnet Type:

Inside spring

### **Bonnet Attachment Method:**

Threaded

## **Disk Loading Method:**

Spring

### **Bolt Hole Quantity:**

4 all ends

#### Valve Operation Method:

Automatic

#### Flange Shape:

Round with holes all ends

#### Connection Type:

Flange all ends

#### Valve Size:

1.250 inches

## Adjustable Pressure Range:

+30.0 to 100.0 pounds per square inch

### **Outside Diameter:**

5.250 inches all ends

#### Thickness:

0.750 inches all ends

## First Connection Face To Centerline Distance:

3.750 inches

#### **Bolt Hole Diameter:**

0.750 inches all ends

## Second Connection Face To Centerline Distance:

3.750 inches

# Bolt Circle Diameter:

3.875 inches all ends

# Flange Face Design:

Raised straight all ends

# Raised Face Height:

0.062 inches all ends

# Raised Face Diameter:

2.500 inches all ends

Material:

Copper alloy body

# Style Designator:

C1a angle flanged ends



# NSN 4820-01-233-4773

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

