NSN 4820-01-235-9744

Butterfly Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-235-9744

| Valve Operation Method: |
|--|
| Manual |
| Flange Shape: |
| Round all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 6.0 inches |
| Criticality Code Justification: |
| Feat |
| Outside Diameter: |
| 5.760 inches all ends |
| Thickness: |
| 0.813 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Butterfly Valve Size: |
| 6.0 inches |
| Special Features: |
| Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us |
| navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the |
| successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, |
| tolerances/clearances, electronic characteristics, and metallurgical properties will be pecified for government q ar (quality assurance |
| representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts |
| Material: |
| Nickel alloy flow control device |
| Material Specification: |
| Qq-n-286 federal specification single material response stem |
| Style Designator: |
| A1 straight thru |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| Mil-std (military Standard): |
| Mil-b-24480 spec. |