## NSN 4820-01-237-2804

Safety Relief Valve - Page 1 of 2

**Flow Control Device:** 

**Bonnet Type:** 

Disk

View Online at https://aerobasegroup.com/nsn/4820-01-237-2804



## Inside screw **Bonnet Attachment Method:** Bolted **Bolt Hole Quantity:** 6 1st end **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** Socket (tube) err-100 Valve Operation Method: Automatic Flange Shape: Round with holes 1st end **Connection Type:** Unthreaded internal tube 2nd end Adjustable Pressure Range: +48.0/+59.0 pounds per square inch Maximum Operating Pressure: 150.0 pounds per square inch single response **Outside Diameter:** 2.375 inches 1st end Thickness: 0.438 inches 1st end **Bolt Hole Diameter:** 0.562 inches 1st end **Bolt Circle Diameter:** 4.438 inches 1st end Flange Face Design: Plain 1st end **Outside Diameter Tube Accommodated:** 2.000 inches 2nd end Material: Stainless steel stem **Material Specification:** Qq-n-281 federal specification single material response stem Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090

## NSN 4820-01-237-2804

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0