NSN 4820-01-237-2832

Calibrated Flow Valve - Page 1 of 2

First End Flange Outside Diameter:

Body Material:

Iron, cast

7.000 inchesBody Style:Straight thru



View Online at https://aerobasegroup.com/nsn/4820-01-237-2832

| Stem Material: |
|--|
| Steel, corrosion resisting |
| Media For Which Designed: |
| Water |
| First End Connection Type: |
| Plain face flange |
| First End Style Designator: |
| Plain |
| First End Flange Shape Style: |
| Round w/ bolt holes |
| First End Flange Thickness: |
| 0.688 inches |
| First End Bolt Hole Quantity: |
| 4 |
| First End Bolt Hole Diameter: |
| 0.750 inches |
| First End Bolt Circle Diameter: |
| 5.500 inches |
| Second End Relationship With First End: |
| Identical |
| Seat Material: |
| Bronze and steel, corrosion resisting |
| Face To Face Distance: |
| 11.000 inches |
| Flow Control Device: |
| Plug |
| Flow Control Device Material: |
| Bronze |
| End Connection Quantity: |
| 2 |
| Valve Discharge Flow Rate: |
| 10.0 gallons per minute and 280.0 gallons per minute |
| Regulation Type: |
| Automatic single stage |
| Shelf Life: |
| N/a |
| |
| |

NSN 4820-01-237-2832

Calibrated Flow Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100