NSN 4820-01-237-6169

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-237-6169 **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Disk Loading Method:** Spring **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **Connection Style:** G46b plain (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external pipe all ends Adjustable Pressure Range: +0.5/+140.0 pounds per square inch **Maximum Operating Pressure:** 400.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Opening Pressure Setting:** 80.0 pounds per square inch Material: Aluminum alloy **Material Specification:** Qq-a-225/6 federal specification single material response body Media For Which Designed: Gas, inert single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 type 1 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-01-237-6169

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.