NSN 4820-01-238-5950

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-238-5950

melas opinig	
Bonnet Attachment Method:	
Bolted	
Bolt Hole Quantity:	
8 2nd end	
Maximum Operating Temp:	
425.0 degrees fahrenheit single response	
Valve Operation Method:	
Automatic	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
4.000 inches	
Adjustable Pressure Range:	
+59.0/+72.0 pounds per square inch	
Maximum Operating Pressure:	
250.0 pounds per square inch single response	
Outside Diameter:	
12.500 inches 1st end	
Thickness:	
1.438 inches 1st end	
First Connection Face To Centerline Distance:	
8.000 inches	
Bolt Hole Diameter:	
0.875 inches all ends	
Second Connection Face To Centerline Distance:	
7.688 inches	
Bolt Circle Diameter:	
7.875 inches 2nd end	
Flange Face Design:	
Plain all ends	
Material:	
Stainless steel stem	
Media For Which Designed:	
Water-oil-gas single response	
Style Designator:	
Err-090	

NSN 4820-01-238-5950

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0