

View Online at <https://aerobasegroup.com/nsn/4820-01-240-1022>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Maximum Operating Temp:

406.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

300.0 pounds per square inch 2nd response

Thread Size:

2.000 inches all ends

Material:

Plastic polytetrafluoroethylene packing

Material Specification:

Astm b-62 assn standard single material response seat

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

Item has been reviewed for asbestos material. The current approved sources 12168 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Npt all ends

Specification Data:

59646-mss-sp-80 manufacturers standard

Specification Or Standard:

150 class and a end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0