NSN 4820-01-240-3018

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-240-3018

Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Oliver perry class ffg
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+57.0/+64.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
6.000 inches 2nd end
Thickness:
0.625 inches 1st end
Bolt Hole Diameter:
0.750 inches all ends
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Media For Which Designed:
Water, salt 2nd response
Style Designator:
Err-090

NSN 4820-01-240-3018

Safety Relief Valve - Page 2 of 2



_					
٠.	h	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0