## NSN 4820-01-240-6084

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-240-6084 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Inverted flare (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 18 2nd end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end Seat Angle: 24.0 degrees all ends **Opening Pressure Setting:** 2.0 pounds per square inch **Special Features:** Used on c-5b acft Material: Steel comp 440c flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment: Passivate Style Designator:** Straight thru **Thread Series Designator:** Unj all ends

N/a

Shelf Life:

## NSN 4820-01-240-6084

Check Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A530b0