NSN 4820-01-240-6088

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-240-6088



Flow Control Device: Disk Bonnet Type: Inside spring Bonnet Attachment Method: Threaded Bolt Hole Quantity: 4 all ends Maximum Operating Temp: 165.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.250 inches

Adjustable Pressure Range:

+45.0/+70.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

4.625 inches all ends

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

3.312 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

3.312 inches

Bolt Circle Diameter:

3.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

2.500 inches all ends

Material:

Stainless steel stem

NSN 4820-01-240-6088

Safety Relief Valve - Page 2 of 2

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

