

View Online at <https://aerobasegroup.com/nsn/4820-01-240-8334>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Bolt Hole Quantity:

12 all ends

Maximum Operating Temp:

165.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

6.000 inches

Adjustable Pressure Range:

+30.0/+50.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

10.125 inches all ends

Thickness:

0.563 inches all ends

First Connection Face To Centerline Distance:

8.125 inches

Bolt Hole Diameter:

0.688 inches all ends

Second Connection Face To Centerline Distance:

9.625 inches

Bolt Circle Diameter:

8.875 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

8.500 inches all ends

Special Features:

Model 1384

Material:

Nickel alloy stem

Material Specification:

Qq-n-298 federal specification single material response seat

Media For Which Designed:

Water, salt single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0