NSN 4820-01-242-5084

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-242-5084

Thread Direction: Right-hand 1st end Flow Control Device: Poppet Bonnet Type: Inside spring Bonnet Attachment Method: Threaded Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Pow Control Device: Poppet Bonnet Type: Inside spring Bonnet Attachment Method: Threaded Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Nat Materi Na Dist Drift Measure: Na Dist Of Measure: Toread Series Designator: Nat Dist Of Measure: Toread Series Designator: Na Dist Of Measure:	Thread Direction:
Poppet Bonnet Type: Inside spring Bonnet Attachment Method: Threaded Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Err-090 Thread Series Designator: Npt 1st end Shaft Life: Na	Right-hand 1st end
Bonnet Type:Inside springBonnet Attachment Method:ThreadedDisk Loading Method:SpringConnection Style:G9 plain, optional en (pipe) 1st endValve Operation Method:AutomaticConnection Type:Threaded internal pipe 1st endMaximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.750 inches 2nd endOpening Pressure Setting:14.7 pounds per square inchMaterial:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Intread Series Designator:Npt 1st endShelf Life:NaMatInt of Measure:Pemilitarization:NoFiig:	Flow Control Device:
Inside spring Bonnet Attachment Method: Threaded Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Style Designator: Npt 1st end Shelf Life: Na Unit Of Measure: T Demilitarization: No	Poppet
Bonnet Attachment Method:ThreadedDisk Loading Method:SpringConnection Style:G9 plain, optional en (pipe) 1st endValve Operation Method:AutomaticConnection Type:Threaded internal pipe 1st endMaximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.750 inches 2nd endOpening Pressure Setting:14.7 pounds per square inchMaterial:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Pro90Thread Series Designator:NyfShelf Life:N/aUnit Of Measure:ToPomilitarization:NoFiig:	Bonnet Type:
Threaded Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Frr-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: T Demilitarization: No Fig:	Inside spring
Disk Loading Method:SpringConnection Style:G9 plain, optional en (pipe) 1st endValve Operation Method:AutomaticConnection Type:Threaded internal pipe 1st endMaximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.750 inches 2nd endOpening Pressure Setting:14.7 pounds per square inchMaterial:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Fr-090Thread Series Designator:Nyt 1st endShelf Life:N/aUnit Of Measure:Pomilitarization:NoFiig:	Bonnet Attachment Method:
Spring Connection Style: G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Fr-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: 	Threaded
Connection Style:G9 plain, optional en (pipe) 1st endValve Operation Method:AutomaticConnection Type:Threaded internal pipe 1st endMaximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.750 inches 2nd endOpening Pressure Setting:14.7 pounds per square inchMaterial:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Npt 1st endShelf Life:N/aUnit Of Measure:NoFiig:	Disk Loading Method:
G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Spring
Valve Operation Method:AutomaticConnection Type:Threaded internal pipe 1st endMaximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.750 inches 2nd endOpening Pressure Setting:14.7 pounds per square inchMaterial:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Frr-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:Pemilitarization:NoFiig:	Connection Style:
Automatic Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Fr-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Init Of Measure: Demilitarization: No	G9 plain, optional en (pipe) 1st end
Connection Type: Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Valve Operation Method:
Threaded internal pipe 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Automatic
Maximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.750 inches 2nd endOpening Pressure Setting:14.7 pounds per square inchMaterial:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Err-090Thread Series Designator:Nyt 1st endShelf Life:N/aDemilitarization:NoFig:	Connection Type:
200.0 pounds per square inch single response Thread Size: 0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: 	Threaded internal pipe 1st end
Thread Size:0.750 inches 2nd endOpening Pressure Setting:14.7 pounds per square inchMaterial:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Err-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Maximum Operating Pressure:
0.750 inches 2nd end Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	200.0 pounds per square inch single response
Opening Pressure Setting: 14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Size:
14.7 pounds per square inch Material: Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.750 inches 2nd end
Material:Steel comp 316 bodyMedia For Which Designed:Gas, inert 3rd responseStyle Designator:Err-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Opening Pressure Setting:
Steel comp 316 body Media For Which Designed: Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	14.7 pounds per square inch
Media For Which Designed:Gas, inert 3rd responseStyle Designator:Err-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:
Gas, inert 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp 316 body
Style Designator:Err-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Media For Which Designed:
Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Gas, inert 3rd response
Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Err-090
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Npt 1st end
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A046b0	Fiig:
	A046b0