NSN 4820-01-242-5339

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-242-5339 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 7.0 gallons per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side **Adjustable Pressure Range:** +500.0/+825.0 pounds per square inch **Maximum Operating Pressure:** 500.0 pounds per square inch single response **Thread Size:** 0.562 inches all ends **Opening Pressure Setting:** 500.0 pounds per square inch Media For Which Designed: Hydraulic fluid, petroleum base single response **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends **Specification Data:** 96906-ms28893 government standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4820-01-242-5339

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0