NSN 4820-01-242-9961

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-242-9961

Thread Direction:Right-hand 1st endRight-hand 1st endFlow Control Device:PoppetDisk Loading Method:SpringMaxinum Operating Temp:250.0 degrees fahrenheit single responseConnection Style:G46b plain (pipe) 1st endValve Operation Method:AutomaticConnection Type:Threaded external pipe all endsMaxinum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.375 inches 1st endOpening Pressure Setting:10.0 pounds per square inchMaterial:Steel comp 316Media For Which Designed:Hydrogen 4th responseStyle Designator:Irr-090Thread Series Designator:Ny1 1st endShelf Life:N/aUnit of Measure:"Pomilitarization:NoFiig:Au4660	View Online at https://aerobasegroup.com/nsn/4820-01-242-996
Fow Control Device:PoppetPoppetDisk Loading Method:SpringMaximum Operating Temp:250.0 degrees fahrenheit single responseConnection Style:G46b plain (pipe) 1st endValve Operation Method:AutomaticConnection Type:Threaded external pipe all endsMaximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.375 inches 1st endOpening Pressure Setting:10.0 pounds per square inchMaterial:Steel comp 316Media For Which Designed:Hydrogen 4th responseStyle Designator:Err-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Thread Direction:
Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style: G46b plain (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Right-hand 1st end
Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style: G48b plain (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Na Fig:	Flow Control Device:
Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style: G48b plain (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: No Fig:	Poppet
Maximum Operating Temp:250.0 degrees fahrenheit single responseConnection Style:G46b plain (pipe) 1st endValve Operation Method:AutomaticConnection Type:Threaded external pipe all endsMaximum Operating Pressure:200.0 pounds per square inch single responseThread Size:0.375 inches 1st endOpening Pressure Setting:10.0 pounds per square inchMaterial:Steel comp 316Media For Which Designed:Hydrogen 4th responseStyle Designator:Err-090Thread Series Designator:NyaUnit Of Measure:NaDemilitarization:NoFiig:	Disk Loading Method:
250.0 degrees fahrenheit single response Connection Style: G46b plain (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Spring
Connection Style: G46b plain (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Maximum Operating Temp:
G46b plain (pipe) 1st end Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: - -	250.0 degrees fahrenheit single response
Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Connection Style:
Automatic Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Fhread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: No	G46b plain (pipe) 1st end
Connection Type: Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Valve Operation Method:
Threaded external pipe all ends Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Automatic
Maximum Operating Pressure: 200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Connection Type:
200.0 pounds per square inch single response Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Threaded external pipe all ends
Thread Size: 0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Maximum Operating Pressure:
0.375 inches 1st end Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	200.0 pounds per square inch single response
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Size:
10.0 pounds per square inch Material: Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.375 inches 1st end
Material:Steel comp 316Media For Which Designed:Hydrogen 4th responseStyle Designator:Style Designator:Err-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Opening Pressure Setting:
Steel comp 316 Media For Which Designed: Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	10.0 pounds per square inch
Media For Which Designed:Hydrogen 4th responseStyle Designator:Err-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:NoFig:	Material:
Hydrogen 4th response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp 316
Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Media For Which Designed:
Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hydrogen 4th response
Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Err-090
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Npt 1st end
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A046b0	Fiig:
	A046b0