NSN 4820-01-243-0813

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside spring

Disk

Integral



View Online at https://aerobasegroup.com/nsn/4820-01-243-0813

megrai
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+59.0/+72.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
5.540 inches 2nd end
Thickness:
0.530 inches 1st end
First Connection Face To Centerline Distance:
5.375 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
5.375 inches
Bolt Circle Diameter:
5.000 inches 1st end
Flange Face Design:
Plain all ends
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-243-0813

Safety Relief Valve - Page 2 of 2



Furnished	Items And	Quantity:
-----------	-----------	-----------

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0