NSN 4820-01-244-2368

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-244-2368

| Thread Direction: Right-hand all ends Flow Control Device: Disk Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) all ends Valve Operation Method: Automatic |
|--|
| Flow Control Device: Disk Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) all ends Valve Operation Method: |
| Disk Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) all ends Valve Operation Method: |
| Disk Loading Method: Spring Connection Style: G9 plain, optional en (pipe) all ends Valve Operation Method: |
| Spring Connection Style: G9 plain, optional en (pipe) all ends Valve Operation Method: |
| Connection Style: G9 plain, optional en (pipe) all ends Valve Operation Method: |
| G9 plain, optional en (pipe) all ends Valve Operation Method: |
| Valve Operation Method: |
| • |
| Automatic |
| |
| Connection Type: |
| Threaded internal pipe all ends |
| Thread Size: |
| 0.375 inches all ends |
| Opening Pressure Setting: |
| 1000.0 pounds per square inch |
| Material: |
| Aluminum body |
| Media For Which Designed: |
| Oil, hydraulic single response |
| Thread Series Designator: |
| Npt all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |