NSN 4820-01-244-2372



Calcity Relief Valve 1 age 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-01-244-2372
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Adjustable Pressure Range:
+45.0/+70.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
6.125 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
4.562 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
4.562 inches
Bolt Circle Diameter:
5.000 inches all ends
Flange Face Design:
Plain all ends
Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Water, salt single response

NSN 4820-01-244-2372

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0