

View Online at <https://aerobasegroup.com/nsn/4820-01-246-5970>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Face To Face Distance:

7.000 inches

Thickness:

0.500 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Plain all ends

Special Features:

Locking device on bonnet; stop lift check valve internally

Material:

Copper alloy 865 stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 30263, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0