## NSN 4820-01-246-6276

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-246-6276

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+401.0/+500.0 pounds per square inch
Maximum Operating Pressure:
700.0 pounds per square inch single response
Outside Diameter:
5.000 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
4.750 inches
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Plain all ends
Material:
Plastic polytetrafluoroethylene packing
Style Designator:
, - J

Err-090

## NSN 4820-01-246-6276

Safety Relief Valve - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0