## NSN 4820-01-247-0080

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-247-0080

Bonnet Attachment Method:	
Bolted	
<b>Bolt Hole Quantity:</b>	
8 all ends	
Maximum Operating Temp:	
200.0 degrees fahrenheit single respor	ise
Valve Operation Method:	
Automatic	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
3.000 inches	
Adjustable Pressure Range:	
+48.0/+59.0 pounds per square inch	
Maximum Operating Pressure:	
150.0 pounds per square inch single re	sponse
Outside Diameter:	
9.000 inches 1st end	
Thickness:	
0.500 inches all ends	
First Connection Face To Centerline	Distance:
6.375 inches	
<b>Bolt Hole Diameter:</b>	
0.562 inches all ends	
Second Connection Face To Centerl	ine Distance:
5.750 inches	
<b>Bolt Circle Diameter:</b>	
6.560 inches 1st end	
Flange Face Design:	
Plain all ends	
Material:	
Stainless steel stem	
Media For Which Designed:	
Water-oil-gas single response	
Style Designator:	
Err-090	

## NSN 4820-01-247-0080

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0