NSN 4820-01-247-6909

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-247-6909

View Online at https://aerobasegroup.com/nsn/4820-01-247-6909	
Thread Class:	
3a all ends	
Thread Direction:	
Right-hand all ends	
Flow Control Device:	
Poppet	
Maximum Operating Temp:	
250.0 degrees fahrenheit single response	
Minimum Operating Temp:	
-40.0 degrees fahrenheit	
Connection Style:	
G50 external seat for gasket seal (boss) all ends	
Valve Operation Method:	
Automatic	
Connection Type:	
Threaded external tube all ends	
Thready Qty Per Inch (tpi):	
18 all ends	
Adjustable Pressure Range:	
+0.5/+140.0 pounds per square inch	
Thread Size:	
0.375 inches all ends	
Opening Pressure Setting:	
75.0 pounds per square inch	
Special Features:	
Oxygen service; to be cleaned iaw mil-c-81302	
Material:	
Rubber chloroprene class cr packing	
Material Specification:	
Qq-a-225/6 federal specification single material response body	
Media For Which Designed:	
Oxygen, gaseous single response	
Surface Treatment:	
Anodize	
Surface Treatment Specification:	
Mil-a-8625 type i military specification single treatment response	
Style Designator:	
Err-090	
Thread Series Designator:	
Unj all ends	
Shelf Life:	
NI/a	

N/a

NSN 4820-01-247-6909

Safety Relief Valve - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.