

View Online at <https://aerobasegroup.com/nsn/4820-01-247-7791>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

100.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Valve Size:

5.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

10.000 inches all ends

Face To Face Distance:

14.000 inches

Thickness:

0.750 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

8.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy stem

Material Specification:

Qq-n-281 federal specification single material response stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 30263, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0