Stop-check Valve - Page 1 of 2





Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal

Valve Size:

3.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

7.500 inches all ends

Face To Face Distance:

9.000 inches

Thickness:

0.625 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

6.000 inches all ends

Flange Face Design:

Plain all ends

Special Features:

Stop check type

Material:

Nickel alloy 400 stem

Material Specification:

Qq-n-281 federal specification single material response stem

Media For Which Designed:

Water-oil-gas 2nd response

NSN 4820-01-247-9791

Stop-check Valve - Page 2 of 2



Style Designator:

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 30263 have indicated their part number contained

asbestos prior to 1984, the continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0