NSN 4820-01-248-1433

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-248-1433

Inside spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
66.0 pounds per square inch
Outside Diameter:
5.000 inches all ends
Thickness:
0.562 inches all ends
First Connection Face To Centerline Distance:
4.125 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
4.125 inches
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.875 inches all ends
Material:
Steel
Media For Which Designed:
Water-oil-gas single response

NSN 4820-01-248-1433

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0