NSN 4820-01-248-2432

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-248-2432

Flow Control Device:
Stem
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Connection Style:
Err-090 all ends
Valve Operation Method:
Manual
Connection Type:
Butt weld tube all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Outside Diameter Tube Accommodated:
4.625 inches all ends
Material:
Stainless steel flow control device
Stainless steel flow control device Style Designator:
Style Designator:
Style Designator: Err-090
Style Designator: Err-090 Furnished Items And Quantity:
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece Shelf Life:
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece Shelf Life: N/a
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece Shelf Life: N/a
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece Shelf Life: N/a Unit Of Measure:
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece Shelf Life: N/a Unit Of Measure: Demilitarization:
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece Shelf Life: N/a Unit Of Measure: Demilitarization: No
Style Designator: Err-090 Furnished Items And Quantity: 2 nut and 2 tailpiece Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: