NSN 4820-01-248-3822

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-248-3822

Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+30.0/+50.0 pounds per square inch
Outside Diameter:
7.500 inches all ends
Thickness:
0.625 inches all ends
First Connection Face To Centerline Distance:
5.062 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
5.062 inches
Bolt Circle Diameter:
6.000 inches all ends
Flange Face Design:
Plain all ends
Material:
Rubber seat
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090

NSN 4820-01-248-3822

Safety Relief Valve - Page 2 of 2



Furnished	Items	And	Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0