

View Online at <https://aerobasegroup.com/nsn/4820-01-248-4246>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Maximum Operating Temp:**

406.0 degrees fahrenheit 1st response

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

300.0 pounds per square inch 2nd response

**Thread Size:**

2.500 inches all ends

**Material:**

Plastic polytetrafluoroethylene packing

**Material Specification:**

Astm b-62 assn standard single material response seat

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

Item has been reviewed for asbestos material. The current approved sources 12168 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Npt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0