NSN 4820-01-248-6252

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-248-6252

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+48.0/+59.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
6.620 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
5.750 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
5.750 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-248-6252

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0