Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-251-3129

Body Material: Bronze, astm b61 First End Flange Outside Diameter: 11.000 inches Body Style: Straight thru Media For Which Designed: Water, salt First End Connection Type: Plain face flange First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 11.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches First End Bolt Hole Diameter: 0.875 inches First End Bolt Hole Diameter: 0.875 inches First End Relationship With First End: dentical Second End Relationship With First End: dentical Second End Relationship With First End: Out inches First Of Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device: Disk Flow Control Device: Disk
First End Flange Outside Diameter: 11.000 inches Body Style: Straight thru Media For Which Designed: Water, salt First End Connection Type: Plain face flange First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: B First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches Second End Relationship With First End: dentical Beat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device Material: Rubber, buna-n Flow Control Device Material: Rubber, buna-n End Connection Quantity:
11.000 inches Body Style: Straight thru Media For Which Designed: Water, salt First End Connection Type: Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: B First End Bolt Hole Diameter: 0.875 inches First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Body Syle: Straight thru Media For Which Designed: Water, salt First End Connection Type: Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: B First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 in
Straight thru Media For Which Designed: Water, salt First End Connection Type: Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.2675 inches First End Bolt Circle Diameter: 0.2675 inches First End Bolt Circle Diameter: 0.260 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Water, salt First End Connection Type: Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches First End Bolt Circle Diameter: 0.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Water, salt First End Connection Type: Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
First End Connection Type: Plain face flange First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches Second End Relationship With First End: dentical Second End Re
Plain face flange First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3. First End Bolt Hole Diameter: 0.2875 inches First End Bolt Circle Diameter: 0.2870 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n
First End Style Designator: Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.2675 inches First End Bolt Circle Diameter: 0.260 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Plain First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches First End
First End Flange Shape Style: Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches First End Bolt Circle Diameter: 0.875 inches Second End Relationship With First End: 0.9250 inches Second E
Round w/ bolt holes First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
First End Flange Thickness: 1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 17.000 inches First End Control Device Material: Rubber, buna-n End Connection Quantity:
1.125 inches First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.250 inches Second End Relationship With First End: 0.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
First End Bolt Hole Quantity: 3 First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
First End Bolt Hole Diameter: 0.875 inches First End Bolt Circle Diameter: 0.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
D.875 inches First End Bolt Circle Diameter: D.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
First End Bolt Circle Diameter: 9.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
2.250 inches Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Second End Relationship With First End: dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
dentical Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Seat Material: Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Rubber, buna-n Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Face To Face Distance: 17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
17.000 inches Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Flow Control Device: Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Disk Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Flow Control Device Material: Rubber, buna-n End Connection Quantity:
Rubber, buna-n End Connection Quantity:
End Connection Quantity:
)
-
Outlet Pressure Range:
+7.0/+9.0 pounds per square inch
Regulation Type:
Manual single stage
Manual Control Method:
Screw
/alve Stem Design:
Single seat

Fluid Pressure Regulating Valve - Page 2 of 2

Valve Loading Method: Spring **Remote Actuation Method:** Diaphragm Maximum Inlet Pressure Rating: 250.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A21100

