

View Online at <https://aerobasegroup.com/nsn/4820-01-252-4396>

Body Material:

Steel, corrosion resisting, qq-s-763, class 302, 303, 304, 305, 310, or 316

Outside Surface Treatment:

Passivated

Body Style:

Straight thru

Furnished Items:

Nut

First End Connection Type:

Threaded internal pipe

First End Style Designator:

Plain

First End Thread Size And Series/type Designator:

1/4-18 npt

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Seat Material:

Plastic, polychlorotrifluoroethylene

Packing Material:

Rubber

Flow Control Device:

Disk

End Connection Quantity:

2

Mounting Facility:

Panel

Regulation Type:

Manual single stage

Manual Control Method:

Knob

Valve Loading Method:

Weight

Maximum Inlet Pressure Rating:

6000.0 pounds per square inch

Filter:

Not included

Tempurature Rating:

Between -10.0 degrees celsius and 55.0 degrees celsius

Special Features:

Used on p/n 8431350; aim-9 msl; storage temp range celsius minus 62.0; pos c 85.0; prf pressure 9000 psig minburst pressure 24000 psig min; valve handle black; dim o/a lg 4.087 ino/a w 2.250 in; o/a ht 2.375 in dia

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100