NSN 4820-01-252-4586

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-252-4586

Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+507.0/+565.0 pounds per square inch
Maximum Operating Pressure:
1480.0 pounds per square inch single response
Outside Diameter:
4.625 inches 1st end
Thickness:
0.625 inches 1st end
First Connection Face To Centerline Distance:
3.310 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
3.250 inches
Bolt Circle Diameter:
3.125 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
2.000 inches 2nd end
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-252-4586

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0