## NSN 4820-01-252-7819

Exhaust Control Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-252-7819

| Flow Control Device:                                       |
|--|
| Disk   |
| Bonnet Type:   |
| Outside screw-yoke   |
| Bonnet Attachment Method:                                  |
| Bolted   |
| Bolt Hole Quantity:  |
| 8 all ends   |
| Valve Operation Method:                                    |
| Manual   |
| Flange Shape:  |
| Round with holes all ends                                  |
| Connection Type:   |
| Flange all ends  |
| Maximum Operating Pressure:                                |
| 150.0 pounds per square inch single response               |
| Outside Diameter:  |
| 8.500 inches 3rd end                                       |
| Thickness:   |
| 0.922 inches all ends                                      |
| Bolt Hole Diameter:  |
| 0.875 inches all ends                                      |
| Bolt Circle Diameter:                                      |
| 8.500 inches all ends                                      |
| Flange Face Design:  |
| Raised straight all ends                                   |
| Raised Face Height:  |
| 0.062 inches all ends                                      |
| Raised Face Diameter:                                      |
| 7.312 inches all ends                                      |
| Special Features:  |
| Valve size for 2 ends is 5.250 in.; other end is 3.750 in. |
| Material:  |
| Steel flow control device                                  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |

A046b0