NSN 4820-01-255-6158

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-255-6158

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Pressure seal, ring type
Disk Loading Method:
Spring
Maximum Operating Temp:
165.0 degrees fahrenheit single response
End Application:
Usns henry j. Kaiser class tao
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
Adjustable Pressure Range: +1401.0/+2900.0 pounds per square inch
-
+1401.0/+2900.0 pounds per square inch
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure:
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features:
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material:
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed:
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response Style Designator:
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response Style Designator: Err-090
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response Style Designator: Err-090 Shelf Life:
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response Style Designator: Err-090 Shelf Life: N/a
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response Style Designator: Err-090 Shelf Life: N/a
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response Style Designator: Err-090 Shelf Life: N/a Unit Of Measure:
+1401.0/+2900.0 pounds per square inch Maximum Operating Pressure: 3450.0 pounds per square inch 1st response Special Features: Adjustment lever included Material: Stainless steel Media For Which Designed: Air single response Style Designator: Err-090 Shelf Life: N/a Unit Of Measure: Demilitarization: