NSN 4820-01-256-5156

Calibrated Flow Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-256-5156

| Body Material: | |
|---|--|
| Brass | |
| Body Style: | |
| Straight thru | |
| Media For Which Designed: | |
| Water, salt | |
| First End Connection Type: | |
| Unthreaded internal pipe | |
| First End Style Designator: | |
| Socket w/brazing ring | |
| First End Pipe Size Accommodated: | |
| 1.500 inches | |
| Second End Relationship With First End: | |
| Identical | |
| Seat Material: | |
| Copper alloy | |
| Flow Control Device: | |
| Diaphragm | |
| Flow Control Device Material: | |
| Rubber, synthetic | |
| End Connection Quantity: | |
| 2 | |
| Valve Discharge Flow Rate: | |
| 23.0 gallons per minute | |
| Renewable Seat Ring Type: | |
| Retaining ring | |
| Regulation Type: | |
| Automatic single stage | |
| Maximum Inlet Pressure Rating: | |
| 150.0 pounds per square inch | |
| Tempurature Rating: | |
| 160.0 degrees fahrenheit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A21100 | |
| | |