NSN 4820-01-258-1039

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Outside screw-yoke

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-258-1039

Bonnet Attachment Method:					
Bolted					
Bolt Hole Quantity:					
4 all ends					
Maximum Operating Temp:					
250.0 degrees fahrenheit single response					
Valve Operation Method:					
Automatic					
Flange Shape:					
Round with holes all ends					
Connection Type:					
Flange all ends					
Valve Size:					
1.000 inches					
Adjustable Pressure Range:					
+40.0/+48.0 pounds per square inch					
Maximum Operating Pressure:					
400.0 pounds per square inch single response					
Outside Diameter:					
4.250 inches all ends					
Thickness:					
0.375 inches all ends					
First Connection Face To Centerline Distance:					
3.625 inches					
Bolt Hole Diameter:					
0.562 inches all ends					
Second Connection Face To Centerline Distance:					
3.625 inches					
Bolt Circle Diameter:					
3.120 inches all ends					
Flange Face Design:					
Plain all ends					
Material:					
Stainless steel stem					
Media For Which Designed:					
Water-oil-gas single response					
Style Designator:					
Err-090					

NSN 4820-01-258-1039

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0