## NSN 4820-01-258-2698

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-258-2698

Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Weight
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Opening Pressure Setting:
140.0 pounds per square inch
Outside Diameter:
6.125 inches all ends
Thickness:
0.937 inches all ends
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.687 inches all ends
Second Connection Face To Centerline Distance:
5.500 inches
Bolt Circle Diameter:
5.000 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 federal specification single material response seat
Media For Which Designed:
Water-oil-gas single response

## NSN 4820-01-258-2698

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0