NSN 4820-01-258-2698

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk

View Online at https://aerobasegroup.com/nsn/4820-01-258-2698



Inside screw **Bonnet Attachment Method:** Bolted **Disk Loading Method:** Weight **Bolt Hole Quantity:** 6 all ends Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 2.500 inches **Opening Pressure Setting:** 140.0 pounds per square inch **Outside Diameter:** 6.125 inches all ends Thickness: 0.937 inches all ends **First Connection Face To Centerline Distance:** 5.500 inches **Bolt Hole Diameter:** 0.687 inches all ends **Second Connection Face To Centerline Distance:** 5.500 inches **Bolt Circle Diameter:** 5.000 inches all ends Flange Face Design: Plain all ends Material: Nickel alloy flow control device **Material Specification:** Qq-n-281 federal specification single material response seat Media For Which Designed:

Water-oil-gas single response

NSN 4820-01-258-2698

Safety Relief Valve - Page 2 of 2

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

