## NSN 4820-01-258-5069

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

**Disk Loading Method:** 

Bonnet Type: Inside spring

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-258-5069

Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring (tube) err-100
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 1st end
Connection Type:
Unthreaded internal tube 2nd end
Adjustable Pressure Range:
+164.0/+201.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
3.812 inches 1st end
Thickness:
0.438 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Bolt Circle Diameter:
2.688 inches 1st end
Flange Face Design:
Plain all ends
Outside Diameter Tube Accommodated:
0.750 inches 2nd end
Material:
Stainless steel stem
Material Specification:
Qq-n-281 federal specification single material response seat

## NSN 4820-01-258-5069

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Demilitarizat

No

Fiig:

A046b0