## NSN 4820-01-258-7208

Angle Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-258-7208

Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
366.6 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
5.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
10.000 inches all ends
Thickness:
0.750 inches all ends
First Connection Face To Centerline Distance:
6.250 inches
Bolt Hole Diameter:
0.875 inches all ends
Second Connection Face To Centerline Distance:
6.250 inches
Bolt Circle Diameter:
8.500 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Stop check
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Err-090
Supplementary Features:
This item has been reviewed for asbestos material. The current approved source, 30263, has indicated their part number contained
ashestos prior to 1984. They continue to manufacture the same part number without ashestos material after 1984

## NSN 4820-01-258-7208

Angle Valve - Page 2 of 2



Furnished	Items A	٩nd	Quantity:
-----------	---------	-----	-----------

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0