NSN 4820-01-259-0348

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-259-0348

Disk Loading	Method:
Spring	
Bolt Hole Qua	antity:
8 1st end	
Maximum Op	perating Temp:
250.0 degrees	s fahrenheit single response
Valve Operat	ion Method:
Automatic or r	nanual
Flange Shape	e:
Round with ho	oles all ends
Connection 1	Гуре:
Flange all end	ls
Valve Size:	
3.000 inches	
Adjustable P	ressure Range:
+15.0/+18.0 p	ounds per square inch
Maximum Op	perating Pressure:
150.0 pounds	per square inch single response
Outside Diam	neter:
9.000 inches	1st end
Thickness:	
0.688 inches	1st end
First Connec	tion Face To Centerline Distance:
5.062 inches	
Bolt Hole Dia	meter:
0.750 inches 2	2nd end
Second Conr	nection Face To Centerline Distance:
5.062 inches	
Bolt Circle Di	iameter:
7.500 inches	1st end
Flange Face	Design:
Plain all ends	
Material:	
Stainless stee	el stem
Material Spec	cification:
Qq-n-281 fede	eral specification single material response seat

NSN 4820-01-259-0348

Safety Relief Valve - Page 2 of 2



Media For Which Designed:	
Water-oil-gas single response	
Style Designator:	
Err-090	
Furnished Items And Quantity:	
1 lever	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A046b0