NSN 4820-01-259-2211

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-259-2211

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
75.0 degrees fahrenheit 1st response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+57.0/+62.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
58.0 pounds per square inch
Outside Diameter:
5.000 inches 1st end
Thickness:
0.750 inches 2nd end
First Connection Face To Centerline Distance:
4.875 inches
Bolt Hole Diameter:
0.750 inches 2nd end
Second Connection Face To Centerline Distance:
5.125 inches
Bolt Circle Diameter:
6.000 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.922 inches 2nd end

NSN 4820-01-259-2211

Safety Relief Valve - Page 2 of 2



Raised Face Diameter:
5.000 inches 2nd end
Special Features:
1 pipe plug (body) 1/2inch npt
Material:
Stainless steel flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0