

View Online at <https://aerobasegroup.com/nsn/4820-01-260-6924>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

450.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal

Features Provided:

Bonnet packing

Valve Size:

6.000 inches

Maximum Operating Pressure:

300.0 pounds per square inch 1st response

Outside Diameter:

11.000 inches all ends

Face To Face Distance:

14.000 inches

Thickness:

0.813 inches all ends

Bolt Hole Diameter:

0.875 inches all ends

Bolt Circle Diameter:

9.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy 400 stem

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Supplementary Features:

Uthis item has been reviewed for asbestos material; the current sources, 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0