

View Online at <https://aerobasegroup.com/nsn/4820-01-260-6924>

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

8 all ends

**Maximum Operating Temp:**

450.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Mounting Position:**

Horizontal

**Features Provided:**

Bonnet packing

**Valve Size:**

6.000 inches

**Maximum Operating Pressure:**

300.0 pounds per square inch 1st response

**Outside Diameter:**

11.000 inches all ends

**Face To Face Distance:**

14.000 inches

**Thickness:**

0.813 inches all ends

**Bolt Hole Diameter:**

0.875 inches all ends

**Bolt Circle Diameter:**

9.500 inches all ends

**Flange Face Design:**

Plain all ends

**Material:**

Nickel alloy 400 stem

**Media For Which Designed:**

Steam single response

**Style Designator:**

Straight through flanged ends

**Supplementary Features:**

Uthis item has been reviewed for asbestos material; the current sources, 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0