## NSN 4820-01-260-6927

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-260-6927

Flow Collifor Device.
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
<b>Bolt Hole Quantity:</b>
8 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Adjustable Pressure Range:
+15.0/+18.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
7.688 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
5.812 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
5.812 inches
Bolt Circle Diameter:
6.562 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response

## NSN 4820-01-260-6927

Safety Relief Valve - Page 2 of 2



Style Designator:	
Err-090	
Furnished Items And Quantity:	
1 lever	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A046b0