NSN 4820-01-260-6976

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-260-6976

Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
8.000 inches
Adjustable Pressure Range:
+15.0/+18.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
13.500 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
10.750 inches
Bolt Hole Diameter:
0.875 inches all ends
Second Connection Face To Centerline Distance:
10.750 inches
Bolt Circle Diameter:
11.750 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel stem
Material Specification:
Qq-n-281 federal specification single material response flow control device
Media For Which Designed:
Water-oil-gas single response

NSN 4820-01-260-6976

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0