

View Online at <https://aerobasegroup.com/nsn/4820-01-261-0991>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal

Valve Size:

2.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Face To Face Distance:

7.000 inches

Thickness:

0.500 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Plain all ends

Special Features:

Material copper alloy 865

Material:

Copper alloy 836 flow control device or copper alloy 922 flow control device

Material Specification:

Astm b62 assn standard 1st material response flow control device or astmb61 assn standard 2nd material response flow control device

Style Designator:

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0